

Dosatron D25 Series



Blue = Standard

White = PVDF

Water powered proportional pump without electricity

- Water flow rate 10 – 2500 l/h
- Dosing proportional to water flow
- Optional ON / OFF function, manually
- Adjustable metering from 0,07 – 10%
- Integrated homogenization
- Working pressure 0,3 - 6 bar
- Metering regardless of water pressure, water flow rate and piping length
- Optional by-pass for external metering

Model	Dosing rate
D 25 RE 1500	0,07 - 0,2 %
D 25 RE 09	0,1 - 0,9 %
D 25 RE 2	0,2 - 2 %
D 25 RE 5	1 - 5 %
D 25 RE 10 *	3 - 10 %

Model (external metering)	Dosing rate
D 25 RE 2/ IE	0,2 - 2 %

Model (external metering)

D 25 RE 5/ IE

D 25 RE 10/ IE *

Dosing rate

1 - 5 %

3 - 10 %

* D 25 RE 10 – 2m²/h max., 4 bar max



_ D 25 RE x/ IE

Downloads

- [Dosatron_D25_BA_DEU_2014.pdf](#) (PDF, 634.9 KiB)
- [Dosatron_D25_BA_ENG_2014.pdf](#) (PDF, 480.0 KiB)
- [Dosatron_D25_Info_DEU_2011.pdf](#) (PDF, 6.7 MiB)
- [Dosatron_D25RE2_DOSIERKURVE_INFO_FRA.PDF](#) (PDF, 38.9 KiB)
-

-  [Dosatron D25RE5 DOSIERKURVE INFO FRA.PDF \(PDF, 39.6 KiB\)](#)
-  [Dosatron D25RE10 DOSIERKURVE INFO FRA.PDF \(PDF, 36.0 KiB\)](#)
-  [Dosatron D25RE1500 DOSIERKURVE INFO FRA.PDF \(PDF, 35.0 KiB\)](#)
-  [Dosatron D25_Info_ENG_2011.pdf \(PDF, 2.3 MiB\)](#)
-  [Dosatron D25_RE_2_Deutsch.pdf \(PDF, 341.3 KiB\)](#)
-  [Dosatron D 25 RE 10 Deutsch.pdf \(PDF, 373.0 KiB\)](#)
-  [Dosatron D 25 RE 4 Deutsch.pdf \(PDF, 343.4 KiB\)](#)
-  [Dosatron D 25 RE 5 Deutsch.pdf \(PDF, 370.4 KiB\)](#)
-  [Organische Säuren D 25_Deutsch.pdf \(PDF, 261.1 KiB\)](#)