

## Etatron eOne MA







### eOne diaphragm metering pump

- Pump head made of PVDF, universal resistant
- Power supply 100 - 240V / 50 / 60Hz
- Start / stop input and proportional dosing 1:1
- Higher dosing capacity as eOne Basic
- Level control
- Pump failure alarms (Underload/Overload)

Type	Flow rate at max. pressure			max. pressure (bar)	Pulse settings Imp./1'	Power supply	Power consumption (W)	Current (A)	Weight (Kg)
	l/h	mL/min	mL/Stroke						
0110	1	16,66	0,09	10	180	100-250V	19	1,4	3,0
0216	2	50,00	0,21	16	300	/ 50-60	21	1,4	3,5
0420	4	83,33	0,27	20	300	HZ	21	1,4	3,0
0607	6	83,33	0,34	7	300		28	2	4,5
0710	7	133,33	0,45	10	300		26	1,8	3,5
1012	10	166,66	0,55	12	300		36	1,8	4,5
1505	15	250,00	0,83	5	300		26	1,8	3,5
2007	20	333,33	1,38	7	300		32	1,9	4,7
3005	30	500,00	2,08	5	300		32	1,9	4,7

## Downloads

-  [Etatron\\_eOne\\_MA\\_LDT\\_BA\\_DEU\\_2014.pdf \(PDF, 678.5 KiB\)](#)
-  [Etatron\\_eOne\\_MA\\_BA\\_ITA\\_ENG\\_2014.pdf \(PDF, 1.5 MiB\)](#)
-  [Etatron\\_eOne\\_Info\\_DEU\\_2015.pdf \(PDF, 157.5 KiB\)](#)
-  [Etatron\\_eOne\\_Info\\_ENG\\_2013.pdf \(PDF, 1.0 MiB\)](#)