

Etatron eOne Plus






eOne diaphragm metering pump

- All eOne MF functions
- Controller mode functions (pH, Redox, Cl)
- Ranges: 0.00 to 14.00 "pH"; -1000 - +1400 mV "Redox",
0 - 2, 0 - 20, 0 - 200 ppm "Cl"
- PT 100 temperature input
- 0/4 -20 mA output
- Proximity switch

Type	Flow rate at max. pressure			max. pressure (bar)	Pulse settings Imp./1'	Power supply	Power consumption (W)	Current (A)	Weight (Kg)
	l/h	mL/min	mL/Stroke						
0110	1	16,66	0,09	10	180	100-250V	19	1,4	3,0
0216	2	50,00	0,21	16	300	/ 50-60	21	1,4	3,5
0420	4	83,33	0,27	20	300	HZ	21	1,4	3,0
0607	6	83,33	0,34	7	300		28	2	4,5
0710	7	133,33	0,45	10	300		26	1,8	3,5
1012	10	166,66	0,55	12	300		36	1,8	4,5
1505	15	250,00	0,83	5	300		26	1,8	3,5
2007	20	333,33	1,38	7	300		32	1,9	4,7
3005	30	500,00	2,08	5	300		32	1,9	4,7

Downloads

-  [Etatron_eOne_PLUS_BA_ITA_ENG_FRA_2014.pdf \(PDF, 5.6 MiB\)](#)
-  [Etatron_eOne_Info_DEU_2015.pdf \(PDF, 157.5 KiB\)](#)
-  [Etatron_eOne_Info_ENG_2013.pdf \(PDF, 1.0 MiB\)](#)